

### Hot Water • Electrically Heated

Designed for cleaning in hazardous locations  
**Class I Group C & D : Class II Group F & G**



UL-1203  
 & CAN/CSA 22.2

Heavy duty  
 protective  
 stainless steel  
 frame for  
 lasting endurance

Low water supply  
 cut off

Trigger gun  
 controlled  
 automatic  
 On/Off with  
 time delay

Triplex pump is belt  
 driven to ensure  
 maximum power  
 transfer and minimal  
 maintenance

Stainless steel cabinet  
 for maximum life

Compact size -  
 52"l x 28"w x 45"h

Innovative energy efficient  
 on-demand heat exchanger  
 maintains high heat even after  
 extended use. Eliminates need  
 for water storage tank

Your Local Dealer

Model	PSI	GPM	HP	kw	Outlet Temp °F	440V amp draw	575V amp draw	Shipping Wt/Lbs
3500XP	3000	3.9	7.5	66/72	180	96	80	900

**Standard Features:**

- Downstream injection, applies chemical at low pressure
- 50' steel wire braided pressure hose with couplers

- Insulated trigger controlled gun with safety lock-off and single insulated lance

**Advantages:**

- No refueling
- No ventilation

- No hot exhaust
- No open flame
- No smoke
- No odor
- Sustainable heat rise 140°