

Hot Water • Oil Fired • Belt Drive • Electric

Designed for heavy duty industrial applications.



- Portable
- Stainless steel coil skin
- Auto Start/Stop Timer
- Belt drive to maximize pump life
- Industrial grade components
- Durable polyester powder coat finish for lifelong appearance
- General triplex pump 
- Large capacity fuel tank
- Adjustable pressure
- Adjustable temperature control
- Pressure relief valve relieves excessive system pressure
- CGA certified to CSA B140.11

Model	PSI	GPM	HP	Electrical	BTU's	WT/Lbs	Dimensions
2000	2000	3.6	5.0	230V/1/60	315,000	600	53"Lx28"Wx44"H
2000E6	2300	3.8	6.0	230V/1/60	315,000	600	53"Lx28"Wx44"H
2000/3	2000	3.6	5.0	230/460/575/3	315,000	600	53"Lx28"Wx44"H
3000	3000	3.9	7.5	230V/1/60	315,000	620	53"Lx28"Wx44"H
3000/3	3000	3.9	7.5	230/460/575/3	315,000	600	53"Lx28"Wx44"H

Your Local Dealer:

Standard Features:

- Continuous hot water
- Tandem pneumatic wheels
- Adjustable pressure
- Forged pump head, removable valve caps and ceramic plungers
- Fuel tank 8.8 gallon
- Safety high limit

- Downstream injection, applies chemical at low pressure
- 50' foot steel wire braided pressure hose with couplers
- Hose rack and wand holder
- Insulated trigger controlled gun with safety lock-off and single insulated lance
- Schedule 80-1/2" Coil

- 20 foot power cord

Options:

- Hour meter
- High pressure soap
- Steam mode 285° F
- Stainless steel hood
- Stainless steel base